

R12 REPLAY SERVER

Simplyliveリプレイソリューションは、最も直感的で拡張性の高いシステムです。

R12インスタントスローリプレイシステムは、10入力2出力で拡張性のあるシングル及びデュアルユーザー構成とサーバーネットワーキング機能を備えたRシリーズの最上位機種です。

コンパクトな2RUの筐体と低価格でありながら、全てのSimplylive製品が持っている最高の品質とクリエイティビティな操作性を持っています。

多数のカメラアングルのリプレイを行える様、1人のオペレーターが最大10入力のレコードソースが扱え、より多くの編集及びオペレーター制御が必要な場合2人目のユーザーを追加し、2オペレーターの構成も可能です。

R12は12チャンネルの変更可成な入出力構成により、シングルオペレーターに対しては10入力2出力、デュアルオペレーター用には8入力4出力といった構成変更も簡単に行えます。

さらに拡張性のあるサーバー構成は、より多くのソースやオペレーターを追加する必要がある場合、複数のサーバーのネットワークにより、必要な中継規模に合わせてリプレイのパワーを高めることができます。

多くの機能を持ちながら、ViBoxシリーズシステムで培われた操作性により、全ての機能は明確で使いやすいタッチスクリーンユーザーインターフェイスに集約され、初心者でも数分で操作を習得できます。さらにこのシステムには最適化されたRC-10専用スローモーションリモートコントローラーが付属しており、タッチUIとシームレスに統合して最高の操作環境を提供します。

機能

- リプレイ/スローリプレイ/ハイライト編集
- 映像音声ファイルのInport/Export
- 専用ハードウェアコントローラ (RC-10)
- シングル及びデュアルオペレーター操作
- ネットワーク接続によるR12の複数台接続機能



2RU Hardware Unit



Remote Controller



R12 - Slomo Touch UI



UI Mini PC

R12 Slomo - Single or Dual Operator Solution



Technical Specifications

Video

- ▶ Up to 10x HD SDI Inputs
- ▶ Up to 4x HD SDI Outputs
- ▶ 10in/2out Single User or 8in/4out Dual User
- ▶ Additional I/O Options: NDI, TS UDP, TS RTP or SRT
- ▶ Codec: DNxHD 120/145Mbps

Video Standard

- ▶ HD 720p, 1080i and 1080p, 8-bit

Audio

- ▶ Embedded audio: 16 tracks per video channel (input or output)
- ▶ 128Ch Dante or 64Ch AES67

Storage

- ▶ 5x2TB SSD Internal RAID Storage
- ▶ Upgradable to 5x4TB SSD
- ▶ USB3 connectors for import from / export to external storage

UI Mini PC

- ▶ 2x UI Mini PCs included in the bundle
- ▶ Intel Core i7, 2.8GHz, 16GB RAM, 250GB SSD
- ▶ 110 / 230 V, 120W power supply

Network

- ▶ 2x 1 Gigabit Ethernet port
- ▶ 2x 10 Gigabit Ethernet port

Controller

- ▶ Dedicated Replay Remote Controller (RCU)
- ▶ 2x RCU included in the bundle
- ▶ Optional Touchscreen (not provided)

Protocols

- ▶ GPI control
- ▶ TSL5

Operating System

- ▶ Microsoft Windows 10

Physical

- ▶ 2RU Chassis: HxWxD: 86.8mm (3.42") x 434.0mm (17.09") x 647.1mm (25.48")
- ▶ Weight: 27.3 kg (60.19lb)

Power

- ▶ Redundant Dual 110/230 V, 1100W PSUs



武蔵エスアイ株式会社

〒161-0033 東京都新宿区下落合 3-21-1 NK フジビル 3F

TEL : 03-5996-7455 FAX : 03-5982-4784 <http://www.musashi-si.co.jp>